



Feature	Specifications
Product Name/ Model Number:	EX-10 # 9002810
Brush/ Pad Drive System	
Brush Motor rpm:	2300 rpm
Brush rpm:	1380 rpm
Brush Motor HP:	.25 hp
Brush Motor Amps:	1.5 amps
Brush Length:	13 in / 33.0 cm
Brush/ Diameter:	3.31 in / 8.4 cm
Brush/ Bristle Type:	Offset rows of nylon bristles in a chevron pattern
Chassis/ Body Construction	
Chassis Construction	Corrosion-proof rotationally-molded polyethylene
Metal Parts Coating:	Zinc Plated
Wheel Diameter:	10 in/ 25.4 cm
Wheel Description:	Non-marking gray tread
Dimensions	
Product Height:	34 in/ 86.4 cm
Product Length:	43 in/ 109.2 cm
Product Weight:	98 lb/ 44.8 kg
Product Width:	16 in/ 40.6 cm
Total Power Consumption	10.10-10.0
Amps:	14.5 amps
Voltages:	120 V
Watts:	1740 watts
Approvals:	UL for US and Canada
Power Cord	OE IN OC AND CANADA
Power Cord Length:	50 ft / 15.2 m
Power Cord Type:	16 gauge, safety yellow
Solution System	To gauge, safety yellow
Solution Pump Pressure:	100 ppi/ 600 kPp
	100 psi/ 690 kPa
Solution Pump amps:	1 amp
Pump Flow Rate:	1 gpm / 3.8 L/min
Solution Capacity:	10 gal/ 38 L
Spray Jets:	Dual, quarter turn with large grip
Solution Valve:	Electronic solenoid
Recovery System	10
Vacuum Motor Amps:	13 amps max
Vacuum Motor Hp:	1.8 Hp
Vacuum Motor Stages:	3 stage
Recovery Capacity:	14.5 gal / 54.8 L
Waterlift at Sealed Waterlift	95 ft <sup>3</sup> / min / 2.69 m <sup>3</sup> /min
Airflow at 2 " Orifice:	New of the Confidence of the C
Warranty	5 YEARS ROTATIONALLY-MOLDED POLYETHYLENE BODY 1 YEARS/ 1 YEARS PARTS AND LABOR PLEASE CONTACT TENNANT COMPANY FOR MORE INFORMATION