

Features:

- ▶ **Endless run time**
- ▶ **Ultra High Speed performance**
- ▶ **Adjustable wheel brackets**
- ▶ **Adjustable handle**
- ▶ **Increased productivity**
- ▶ **Ergonomic Design**
- ▶ **EPA & CARB approved**
- ▶ **Cordless operation**

PROPANE
EXCEPTIONAL ENERGY®



The **Talon Series** provides a variety of buffing widths in a high powered propane machine. No need for high voltage electric cords and generators. Run time is 5 to 6 hours per propane cylinder. Engine choices include Kawasaki or Robin. Emissions protected by three-way catalytic muffler. Options include electric clutch or kill switch, Emissions shut down system and Easy Gloss Spray system.

All machines come standard with service alert (hour) meter, 360° floating swivel spin-on pad driver, adjustable handle, aluminum safety-fill fuel cylinder with overfill prevention device (OPD) (UL and DOT approved), and two year warranty.

Designed and manufactured in the U.S.A.

	Talon 2100	Talon 2400	Talon 2700
Production	25,000 sq ft/hour	28,000 sq ft/hour	33,000 sq ft/hour
Engine Speed	3,600 rpm	3,600 rpm	3,600 rpm
Pad Speed	2,000 rpm	1,800 rpm	1,800 rpm
Pad Size	21"	24"	27"
Machine Dimensions	L 56" x W 22" x H 33"	L 54" x W 25" x H 33"	L 61" x W 28" x H 33"
Total Weight	220 lbs	230 lbs	240 lbs

All engines exceed Environmental Protection Agency (EPA) and California Air Resource Board (CARB) regulations for exhaust emissions.