


## 5680 ec-H2O™ Specifications

**BATTERY-POWERED WALK-BEHIND SCRUBBER**  
with ec-H2O™ converted water scrubbing technology

<b>Feature</b>			
<b>Scrubbing System</b>			
Cleaning path (3 paths available)	<b>28-inch/700 mm</b>	<b>32-inch/800 mm</b>	<b>36-inch/900 mm</b>
Solution tank capacity	30 gallon/114 liter		
<b>Solution flow rates: Disk Standard:</b> Cylindrical Standard & Disk Optional Optional (Cylindrical & Disk) Conventional Mode Option	.22 gpm/0.83 lpm .33 gpm / 1.25 lpm & .44 gpm / 1.66 lpm 0–1.5 gpm / 0–5.7 lpm		.30 gpm / 1.1 lpm .44 gpm / 1.66 lpm & .53 gpm/ 2.0 lpm 0–1.5 gpm / 0–5.7 lpm
Scrub head types Scrub head motors (all paths / types) Brush speed Disk/cylindrical Brush down pressure Disk (2-position) Cylindrical (1-position)		Disk or cylindrical (2) 0.75 hp/ 0.5 kW  200 rpm/750 rpm  100 & 200 lb/45.5 & 91 kg 85 lb/39 kg	
Brush/pad driver quantity & dimensions Disk (D) Cylindrical (L x D)	(2) 14-inch/355 mm (2) 28 x 6-inch/ 700 x 150 mm	(2) 16-inch/405 mm (2) 32x 6-inch/ 800 x 150 mm	(2) 18-inch/455 mm (2) 36 x 6-inch/ 900 x 150 mm
<b>Environmental Impact (Annually) *</b>			
Chemical use reduction Packaging reduction Water use reduction	183 gallons 111 lbs 8190 gallons		
<b>Recovery System</b>			
Recovery tank capacity	40 gallon/151 liter (Includes demisting chamber)		
Vacuum fan Motor Stages Water lift	0.8 hp/0.6 KW 3-stage 73-inch/1,855 mm		
<b>Propelling System</b>			
Propel speed (variable to)	3.1 mph/5.0 km/h		
Batteries (36V system, charger included) Standard Optional	(6) 6V, 235 AH (6) 6V, 335 AH		
Gradeability (Ramp climb) Full Empty	6.0° 8.0°		



# 5680 ec-H2O™ Specifications

## BATTERY-POWERED WALK-BEHIND SCRUBBER with ec-H2O™ converted water scrubbing technology

Machine Dimensions / Sound level			
Length	63-inch/1,600 mm		
Width			
Body	28.25-inch/720mm	28.25-inch/720mm	28.25-inch/720mm
Scrub head	30-inch/760 mm	34-inch/865 mm	38-inch/965 mm
Squeegee	37.5-inch/955 mm	42-inch/1,065 mm	45.5-inch/1,155mm
Height	43-inch/1,090 mm		
Net weight			
Less batteries	403 lb/183 kg		
With 235 AH batteries	805 lb/366 kg		
With 335 AH batteries	985 lb/448 kg		
Minimum aisle turn	66.25-inch/1,680 mm	67-inch/1,700 mm	67.5-inch/1,725 mm
Sound level (operator's ear)	75 dBa		
<b>Warranty</b>	Please refer to your local Tennant representative for information.		

\* Estimates based on requiring, at minimum, 1.5 tanks to clean the facility / area per day. 2 oz of chemical per gallon of water and scrubbing 5 times per week or 260 times per year.

ec-H2O is certified to provide high traction by the National Floor & Safety Institute

