



Model 5700EE Specifications

BATTERY-POWERED WALK-BEHIND SCRUBBER
UL EE Labeled

Feature	
Scrubbing System	
Cleaning path	32-inch/800 mm
Solution tank capacity	30 gallon/114 liter
Scrub head types	Disk and cylindrical
Scrub motors	
Disk	(2) 0.6 hp/0.45 kW
Cylindrical	(2) 0.75 hp/0.56 kW
Brush speed	
Disk/cylindrical	320 rpm/750 rpm
Brush down pressure	
Disk	0-200 lb/0-91 kg
Cylindrical	0-90 lb/0-41 kg
Brush/pad driver quantity & dimensions	
Disk (D)	(2) 16-inch/405 mm
Cylindrical (L x D)	(2) 32 x 6-inch/800 x 150 mm
Recovery System	
Recovery tank capacity	40 gallon/151 liter (Includes demisting chamber)
Vacuum fan	
Motor	0.75 hp/0.56 KW
Stages	4-stage
Water lift	55-inch/1,395 mm
Propelling System	
Propel speed (variable to)	3.1 mph/5.0 km/h
Batteries (36 V system, charger included)	(6) 6V, 235 AH
Gradeability (Ramp climb)	
Full / Empty	6.0° / 8.0°
Machine Dimensions / Sound level	
Length	
Disk	64-inch/1,625 mm
Cylindrical	63-inch/1,600 mm
Width	
Body	28.25-in/ 720 mm
Scrub head	
Disk	34-inch/865 mm
Cylindrical	34.25-inch/870 mm
Squeegee	42-inch/1,070 mm
Height	43-inch/1,090 mm
Net weight	
Less batteries	415 lb/188 kg
With batteries (6) 235 AH 6-V	817 lb/371 kg
Minimum aisle turn:	67-inch/1,700 mm
Sound level (operator's ear)	75 dBa
Warranty	Please refer to your local Tennant representative for information.