




Commercial Floor Care Equipment



Model 900 Flood Restoration Unit

Features	Specifications
Product Name: 900 Model Number: 609017	900 609017
Dimensions Width: Height: Length: Weight:	20 in/ 50.8 cm 35 in/ 81 cm 30 in/ 76 cm 90 lb/ 41 kg
Recovery Tank Capacity	16 gal/ 61 L
Total Power Consumption Volts: Amps: Watts:	120 V 17 A 2040 watts
Power Cords	(2) 50 ft/ 15 m
Vacuum Motor Vacuum Motor: Motor Diameter: Motor Volts: Motor Amps: Motor Watts: Motor Stage: Waterlift: Airflow : Type:	1.6 hp 5.7 in/ 14.5 cm 120 V 10.7 A 1242 3 Stage 120 in/ 304.8 cm at sealed orifice 100 cfm/ 2.8 m ³ /h Periphal discharge, single speed, double ball bearing
Discharge Pump Volts: Amps: Watts: Flow Rate: Check Valve:	120 V 4.8 A 890 watts 40 gpm/ 151 L/min Automatic Shutoff
Housing Housing: Metal parts coating:	Rotationally- molded polyethylene Epoxy power coat or zinc plating
Casters	3 in/ 7.6 cm double ball bearing
Standard Equipment Vacuum Hose diameter: Vacuum Hose Length: Vacuum Hose Type: Discharge Hose Diameter: Discharge Hose Length: Discharge Hose Type: Floor Wand Width:	1.5 in/ 3.8 cm 15 ft /4.6 m High Output, chemical resistant 1.5 in/ 3.8 cm 25 ft/ 7.6 m High Output, chemical resistant 13 in/ 33 cm
Warranty	Tennant warrants the rotationally-molded polyethylene housings and parts on all of its machines to be free from defects in materials and workmanship, under normal use and service for ten (10) years to the original end user. Under this warranty, we guarantee the performance of non-polyethylene parts and components to be free from defects for up to three (3) years or 2,500 hours of operation, whichever comes first, to the original end user. Parts replaced or repaired under this warranty are guaranteed for the remainder of the original warranty period. Labor charges are covered for three (3) full years form the date of purchase for Tennant models, provided an authorized Tennant service provider is used for repair.

