# Advance Convertamatic<sup>®</sup>

Walk-Behind Automatic Scrubbers





The Legendary Advance Convertamatic<sup>®</sup> is Reborn





Soft-Touch<sup>™</sup> Paddle System allows operators to depress drive paddle directly to the handle bar without pinching fingers. This patent-pending feature provides maximum machine control, reduction in repetitive-stress injuries, and prevents operator from being pinned between the machine and an obstruction.

## Ideal Applications Include —

- Grocery
- Schools and University
- Healthcare Facilities
- Retail
- Manufacturing Facilities
- Warehouse/Distribution

## Advance Convertamatic®

Walk-Behind Automatic Scrubbers

# The Advance Convertamatic<sup>®</sup> is the Perfect Combination of Simplicity and Flexibility.

All Convertamatics come standard with an integrated Smart Solutions<sup>™</sup> system that allows the machine to operate for 1 hour and 20 minutes per dump & refill cycle with the Convertamatic's 20 gallon (76 L) solution and recovery tanks. At the same time, the integrated Smart Solutions<sup>™</sup> system features pre-set scrub settings that combine solution flow and scrub pressure into simple operator selections for *regular, heavy, or extreme* scrubbing conditions. The combination of these features makes the

Convertamatic<sup>®</sup> the ultimate in One-Touch<sup>m</sup> operation for instant training, increased safety, consistent performance, and maximum run-time.

The Advance Convertamatic<sup>®</sup> family of scrubbers features six scrubbing configurations on a single platform – 24 inch, 26 inch, and 28 inch scrub decks are available in both disc and cylindrical scrub heads. Additionally, all six scrub decks are tools-free interchangeable on any machine. This modularity allows the flexibility to use either cylindrical sweep/scrub multi-tasking or rotary disc scrubbing with the same machine for different applications at the same facility. In keeping with the Total Clean<sup>™</sup> philosophy, the ability to easily remove the scrub decks also makes the machines easier to service.


The Convertamatic® has many important new safety features:

- Soft-Touch<sup>™</sup> Paddle System allows operators to depress drive paddle directly to the handle bar without pinching fingers.
- UltraFlow<sup>™</sup> Squeegee System provides best-in-class recovery of solution on tight turns to greatly reduce the potential for slippery moisture to be left behind.
- Standard onboard battery charger and optional gel batteries to eliminate battery maintenance, fumes, and acid spills.

#### But that is not all...

Convertamatics also are available with the newest member of the Smart Solutions<sup>™</sup> family. **AXP<sup>™</sup>** is a patent-pending, onboard detergent dispensing system that offers exclusive features and benefits that will redefine onboard detergent dispensing.







Click-off disc scrub heads for productivity and convenience.



Cylindrical scrub decks sweep and scrub in a single pass with dual counter-rotating brushes. Polyethylene hopper eliminates corrosion.

levels on most floor surfaces (15% of scrubbing applications)

non-marking tires

**Regular Scrub** 

surfaces (80% of


**Heavy Scrub** 

For use on moderate soil levels on most floor

scrubbing applications)

For use on heavy soil

Front shroud is no-tools removable for access to scrub motors and for interchanging scrub decks



Tools-free replaceable and height adjustable splash skirt



FEATURES

VALUE



See specifications for dimensions.

## **AXP**<sup>™</sup>

### **Onboard Detergent Dispensing System**

• Ability to quickly switch detergents for multiple applications

• Ability to use any manufacturers' detergent



## **Technical Specifications**

Defining Cleaning	Models	Convertamatic <sup>®</sup> 24D	Convertamatic <sup>®</sup> 26D	Convertamatic <sup>®</sup> 28D	Convertamatic <sup>®</sup> 24C	Convertamatic <sup>®</sup> 26C	Convertamatic <sup>®</sup> 28C
	Scrub Head Type	Disc	Disc	Disc	Cylindrical	Cylindrical	Cylindrical
Innovation	Scrub Path	24 in (61 cm)	26 in (66 cm)	28 in (71 cm)	24 in (61 cm)	26 in (66 cm)	28 in (71 cm)
	Max Productivity	29,600 ft²/hr	32,050 ft²/hr	35,000 ft²/hr	29,600 ft²/hr	32,050 ft²/hr	35,000 ft²/hr
<ul> <li>Our products are designed</li> </ul>	@ 2.8 mph	(2,750 m²/hr)	(3,000 m²/hr)	(3,200 m²/hr)	(2,750 m²/hr)	(3,000 m²/hr)	(3,200 m²/hr)
using innovative technology	Max Productivity	15,800 ft²/hr	17,200 ft²/hr	18,500 ft²/hr	15,800 ft²/hr	17,200 ft²/hr	18,500 ft²/hr
that increases productivity	@ 1.5 mph	(1,468 m²/hr)	(1,598 m²/hr)	(1,719 m²/hr)	(1,598 m²/hr)	(1,598 m²/hr)	(1,719 m²/hr)
and drives down the cost	Scrub Head Size	(2) 12 in (30.5 cm)	(2) 13 in (33 cm)	(2) 14 in (35.5 cm)	(2) 23 in (58 cm)	(2) 25 in (64 cm)	(2) 27 in (69 cm)
to clean.		brushes or pad holders	brushes or pad holders	brushes or pad holders	brushes	brushes	brushes
to clean.	Scrub Pressure						
• You can get expert service	Regular Scrub	max 80 lb (36 kg)	max 80 lb (36 kg)	max 80 lb (36 kg)	max 60 lb (27 kg)	max 60 lb (27 kg)	max 60 lb (27 kg)
and maintenance for your	Heavy Scrub	max 130 lb (59 kg)	max 130 lb (59 kg)	max 130 lb (59 kg)	max 80 lb (36 kg)	max 80 lb (36 kg)	max 80 lb (36 kg)
Advance machines from	Extreme Scrub	max 160 lb (73 kg)	max 160 lb (73 kg)	max 160 lb (73 kg)	max 100 lb (45 kg)	max 100 lb (45 kg)	max 100 lb (45 kg)
	Scrub Head Speed	220 rpm	220 rpm	220 rpm	900 rpm	900 rpm	900 rpm
factory-trained personnel	Solution Flow Rate						
around the world. Fast	Regular Scrub	0.25 gal/min (0.95 L/min) or 80 minutes per solution tank – ALL MODELS					
parts delivery, too.	Heavy Scrub	0.50 gal/min (1.9 L/min) or 40 minutes per solution tank – ALL MODELS					
	Extreme Scrub	0.75 gal/min (2.8 L/min) or 27 minutes per solution tank – ALL MODELS					
Maintain peak performance	Squeegee Width	32.6 in (83 cm)	36.6 in (93 cm)	36.6 in (93 cm)	32.6 in (83 cm)	36.6 in (93 cm)	36.6 in (93 cm)
with Nilfisk Genuine	Dimensions	W = 26 in (66 cm)	W = 27.5 in (70 cm)	W = 30 in (76 cm)	W = 27 in (69 cm)	W = 29 in (74 cm)	W = 31 in (79 cm)
OEM Parts.	(w/o squeegee)	L = 54.5 in (138 cm)	L = 55 in (140 cm)	L = 55.5 in (141 cm)	L = 55 in (140 cm)	L = 55 in (140 cm)	L = 55 in (140 cm)
		H = 44 in (112 cm)	H = 44 in (112 cm)	H = 44 in (112 cm)	H = 44 in (112 cm)	H = 44 in (112 cm)	H = 44 in (112 cm)
<b>Nilfisk</b> Genuine OEM Parts	Weight w/	581 lb (264 kg)	613 lb (278 kg)	613 lb (278 kg)	581 lb (264 kg)	613 lb (278 kg)	613 lb (278 kg)
	Batteries						
	Voltage	24 V – ALL MODELS         (4) 6 V batteries (wet acid and gel cell available) – ALL MODELS					
	Power Source						
	Onboard Battery						
	Charger	24 V, 25 amp wet/gel compatible – ALL MODELS					
	Solution Control	Precision-Flow electric pump – ALL MODELS					
	Solution Tank	20 gal (76 L) – ALL MODELS					
10	Recovery Tank	20 gal (76 L) – ALL MODELS					
	Scrub Motors	(2) 0.50 hp (375 W) – ALL MODELS					
	Vacuum Motor	0.75 hp (560 W) 3-stage – ALL MODELS					
	Sound Level	66 dB A at operator's position – ALL MODELS					
	Drive System	0.4 hp (300 W) variable forward and reverse,					
		max speed = 3 mph (4.83 km/hr), 10% gradeability – ALL MODELS					
Nachine .	Drive Wheels	(2) 7 in (18 cm) diame	eter foam-filled, gray no	on-marking – ALL MOD	ELS		

Specifications are subject to change without notice.

CE D

## **Optional Accessories**

- Onboard Scrub-Vac System
- Multiple Brushes for All Applications
- Maintenance-free, Gel Batteries
- Onboard Tote Bag
- Extended Scrub (Recycling) System





Onboard Tote Bag

Onboard Scrub-Vac System



14600 21st Avenue North Plymouth, MN 55447-3408 www.advance-us.com 800-850-5559 Phone: 800-989-6566 Fax:

396 Watline Avenue Mississauga, Ontario, Canada L4Z 1X2 www.nilfisk-advance.com Phone: 800-668-8400 or 905-712-3260 800-263-5111 or 905-712-3255 Fax:

©2006, Nilfisk-Advance, Inc., Printed in U.S.A., Form L1652A 7-06