



Burnishers & Floor Machines

2510/2550

Battery Burnishers

- Wide 20 inch path
- Cover 21,000 ft²/hr
- Battery operated
- Durable polyethylene body
- Over 2.5 hours of continuous run time per charge
- Adjustable pad pressure 15-40 lbs.
- Dust control system



2370

Dust Control High Speed Floor Burnisher

- 2000 rpm burnishing speed
- Built-in dust collection system
- 20 inch burnishing path
- Floating head for even burnishing
- Fold over handle for storage
- Durable polyethylene body



2300/2320/2340

High Speed Floor Burnishers

- 1200/1600/2000 rpm models
- 75 ft. power cord comes standard
- 20 inch burnishing path
- Twist grip operation with safety locks
- Height adjustable controls
- Durable polyethylene body



2260/2270

Dual Speed Floor Machines

- Dual speed at 185/330 rpm
- Scrub or buff floors
- 17 and 20 inch path models
- Twist grip operation with safety locks
- Height adjustable controls
- Durable polyethylene body



2100 Series

Low Speed Floor Machines

- Choose 13, 17 or 20 inch models
- 180 or 240 rpm speeds
- Safety lock controls
- Ergonomic squeeze grips
- Quiet operation-65 dBA
- Heavy duty models available
- Off-center motor for extended reach
- Adjustable height control



Burnishers & Floor Machines Specifications

Model Number	2510/2550	2370	2300/2320*/2340*	2260/2270
Model type	Pad Assisted/Drive Assisted	HD/High Speed/DC	HD/High Speed	HD/Dual Speeds
Product width	24"/610 mm	22.5"/570 mm	20"/508 mm	17"/432 mm/20"/508 mm
Product height	40"/1016 mm	47.5"/1210 mm	49"/1245 mm	48.75"/1240 mm
Operation voltage	(3) 12 V/215 AH batteries	120 V/15 A	120 V/15 A	120 V/13.5 A
Rated output	3 hp/2238 W	1.5 hp/1400 W	1.5 hp/1100 W	1.5 hp/1100 W
Speed	2000 rpm (nominal)	2000 rpm	1200/1600/2000 rpm	170/310 rpm
Application pressure	(Variable) to 40 lbs/in ² (413 kg/m ²)	NA	NA	NA
Cord length	NA	75'/23 m	75'/23 m	50'/15 m
Operation weight	525 lbs/243 kg	80 lbs/36 kg	68 lbs/30 kg	81.5 lbs/37 kg/84.5 lbs/38 kg
Noise level	70 dBa	66 dBa	75 dBa	65/74 dBa

Optional Accessories: 2510/2550: Field installed flashing safety lights, safety switch, auto stop, parking brake, low voltage shut-off, hour meter and power cut-off. 2160-2360: 3 gal/12 L solution tank, Dyna Scrub Brush, Strata-Grit Brush, Shampoo Brush, Wood Sanding Block

* Not available in Canada

2100 Series Specifications

Model Numbers	2150	2140	2130	2120	2100
Model type	Heavy Duty	Heavy Duty	Standard	Standard	Standard
Operation width	20 in/51 cm	17 in/43 cm	20 in/51 cm	17 in/43 cm	13 in/33 cm
Operation height	13 in/33 cm	12.6 in/32 cm	11 in/28 cm	9 in/23 cm	9.4 in/24 cm
Clearance height	4.3 in/11 cm	4.7 in/12 cm	4.3 in/11 cm	3.9 in/10 cm	3.5 in/9 cm
Operation voltage	120 V/60 Hz	120 V/60 Hz	120 V/60 Hz	120 V/60 Hz	120 V/60 Hz
Rated output	1.75 hp 1320 W	1.75 hp 1320 W	1.25 hp 930 W	1.25 hp 930 W	2/3 hp 495 W
Speed	180 rpm	180 rpm	180 rpm	180 rpm	240 rpm
Brush application pressure	.51lbs/in ² (.35N/cm ²)	.75lbs/in ² (.52N/cm ²)	.41lbs/in ² (.28N/cm ²)	.54lbs/in ² (.37N/cm ²)	.68lbs/in ² (.47N/cm ²)
Cord length	41ft/12.5 m	41ft/12.5 m	41ft/12.5 m	41ft/12.5 m	41ft/12.5 m
Operation weight	130 lbs/59 kg	115 lbs/52 kg	101 lbs/46 kg	88 lbs/40 kg	66 lbs/30 kg
Noise level	65 dBa	65 dBa	65 dBa	65 dBa	65 dBa

Optional Accessories: 3 gal/12 L solution tank, Dyna Scrub Brush, Strata-Grit Brush, Shampoo Brush, Wood Sanding Block

Creating a cleaner, safer world™

Tennant Company offers the most complete line of floor and surface maintenance equipment, floor coatings, brushes and cleaning detergents in the world for the industrial, commercial and outdoor cleaning markets. Our sales and service networks provide you with integrated custom cleaning solutions to meet any floor care need.



Tennant Company Commercial Products

12875 Ransom Street • Holland, MI 49424
Toll-free: (800) 982-7658 • (616) 786-2330
Fax: (800) 678-4240 • www.tennantco.com
Email: tennantinfo@aol.com

Authorized Tennant Distributor