



Model E5 Specifications

SELF-CONTAINED CARPET EXTRACTOR

Feature	English / Metric
Brush Drive System	
Brush bristle length	0.9 in / 23 mm
Brush bristle type	Nylon construction, Reverse chevron
Brush diameter	3.5 in / 89 mm
Brush length	15 in / 380 mm
Brush motor power	.4 hp / .30 kW
Brush motor voltage	120 V / 230 V
Brush RPM	1,200 rpm
Motor RPM	2,400 rpm
Chassis/Body Construction	
Chassis construction	Cast aluminum frame, rotational molded tanks and injection molded plastic cover
Wheel descriptions (non-marring)	8 in / 200 mm
Vacuum System	
Airflow at orifice	99 cfm / 2.8 m ³ /min
Vacuum motor amps	7.1 amps (120V) / 3.6 amps (230V)
Vacuum motor power	1.2 hp / .89 kW
Vacuum motor stages	2 stage
Sealed waterlift	86 in / 2,180 mm
Machine Dimensions (Handle folded flat for storage)	
Length	27 in / 690 mm
Machine Width	19 in / 480 mm
Height	28 in / 710 mm
Weight	102 lb / 46 kg
Solution & Recovery System	
Solution tank capacity	5 gal / 19 L
Recovery tank wet capacity	5 gal / 19 L
Spray jet count	2-quick connect
Power Consumption	
Amps	10.8 amps (120V) / 5.4 amps (230V)
Voltage	120 V / 230 V
Watts	1.74 hp / 1.3 kwatts
Cord	50 ft / 15 m
Electrical Safety Approvals	ETL Tested for UL & CSA Standards
Pump System	
Solution pump pressure	65 psi / 4.48 bar
Solution pump amps	.7 amp (120V) / .35 amp (230V)
Solution pump flow rate	.7 gpm / 2.6 L/min
Sound Level*	
Decibel rating @ operators ear	69 dBA
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.

* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA