



The Maxi II™ 35 wet/dry vacuum exceeds cleaning expectations with increased versatility, enhanced power and cost-efficient performance.

Flexible operation

The Maxi II™ 35 delivers unprecedented cleaning flexibility. When dirt or dust is the primary issue, the Maxi II-35 offers quality filtration and dust capture, in addition to crevice and dusting tools. Operators can also employ the Maxi II-35 for wet applications.

Superior filtration

Featuring a unique filter system, the Maxi II-35 offers one solution for both wet and dry filtration. Designed with three durable components, the filter completely seals entry to the motor, protecting the motor from dust, debris, water or other liquids. Once the job is complete, the filter can be easily lifted out of the vacuum for a simple rinse, then replaced and ready for the next job in a matter of minutes.

Easy operation

The Maxi II-35 wet/dry vacuum offers simple and reliable operation. The lightweight design ensures easy transportation. For enhanced performance, the Maxi II-35 offers a variety of standard accessories, ranging from hoses and wands to squeegees and dusting tools.

Maxxi II™ 35

Wet/Dry Vacuum

- **Quality filtration** ensures superior performance and keeps the motor dry
- **Powerful motor** maximizes cleaning performance
- **Accessories** help tackle diverse cleaning challenges



Trusted. Reliable. Efficient.

Clarke®

SPECIFICATIONS		Maxxi II™ 35
Part Number		107409095
Power		120 V / 60 Hz
Power Cord Length		50 ft (15 m)
Power PMAX		1,100 W
Suction Power End of Tube		220 W
Airflow		101 CFM (45 L/Sec)
Vacuum at Nozzle		72 in of H ₂ O (20 kPa)
Sound Pressure Level		81 dB A
Tank Capacity		9 gal (35 L)
Dust Bag Capacity (Dry)		4 gal (18 L)
Wet Filter Area		163 in ² (1,051 cm ²)
Cartridge Filter Area		321 in ² (2,070 cm ²)
Hose Length		6 ft (1.9 m)
Hose Inlet		~1.25 in (32 mm)
Length x Width x Height		19 in x 17 in x 29 in (46 cm x 42 cm x 73 cm)
Weight		25 lb (11.5 kg)
Tube Holder		included
Accessory Storage		included
Dual Filter System		included

Specifications are subject to change without notice.



Filter system

Unique filter system protects the motor from water, while ensuring complete wet and dry filtration. It is designed with the following components:

- Dry cartridge filter keeps water away from the motor and is waterproof and washable for increased durability
- Red panel holds floater and prevents water overflow
- Blue panel mesh wet filter dissipates foam and is the first dust filter



Motor head

Hinged-motor head quickly lifts off for easy service.



Accessories

The Maxxi II-35 features a variety of standard and optional accessories, including: hose, wand, squeegee floor tool, brush floor tool, crevice tool and dusting tool.

Applications

- Schools and Universities
- Hospitals/Healthcare Facilities
- Grocery Stores
- Retail Outlets
- Arenas and Stadiums
- Automobile Dealerships

Accessories

- Floor Nozzle Rubber Strip
- Floor Nozzle Brush Tool
- Crevice Tool
- Extension Tube/Wand
- Hose
- Cartridge Filter
- Wet Filter
- Tubeholder



©2014 Nilfisk, Inc. All rights reserved. P/N L3318C 2/14

9435 Winnetka Avenue North • Brooklyn Park, MN 55445
Phone: 800.253.0367 • Fax: 800.825.2753

240 Superior Boulevard • Mississauga, Ontario, Canada L5T 2L2
Phone: 800.668.8400 • Fax: 800.263.5111

Clarke®

www.clarkeus.com