


Maintenance guide



Armada BRC 40/22 C



- 1 Drain and clean the solution tank.
- 2 Drain and clean recovery tank.
- 3 Clean the float shut off.
- 4 Clean the brush and vacuum shoe. Inspect the brush for wear and replace if necessary.
- 5 Store brush in the recovery tank with the bearing side up.
- 6 Remove the three spray jets and soak them in a solution of water and vinegar overnight.
- 7 Remove, empty and clean the debris tray.
- 8 Tip machine back to ensure that the extractor deck is resting on the kickstand to protect the brush during storage.

Operation guide



Armada BRC 40/22 C



1 Adjust steering wheel for operator comfort.

2 Fill solution tank.

3 Adjust brush height with yellow knob on extractor deck.

4 Ensure cord is run through cord management system.

5 Use the Kärcher EASY dial to select what operation mode you want to operate in.

6 Press the solution button to activate it. See that water comes through the right but not the left clear dome on the recovery tank.

7 Pull the yellow grip on the steering wheel to begin extraction while walking forward. Apply some resistance to control the speed.

8 Press the black button and pull the yellow grip simultaneously to reverse the operation of the brush.

9 Use the steering wheel to maneuver the machine. Rotate the head 180° for full extraction in corners or tight spaces.