

WINDSOR CHARIOT 3 | EXTRACT 26 DUO



MAINTENANCE

86376040



01) Drain the solution tank.



02) Drain the recovery tank.



03) Rinse and clean out the recovery tank and float shut off.



04) Rinse and clean out the debris collector.



05) Secure the drain hose caps.



06) Replace the hoses in housing.




07) Unlatch and dismantle the vac shoes to clean.

WINDSOR CHARIOT 3 | EXTRACT 26 DUO



MAINTENANCE

86376040



08) **INSPECT BRUSH:** when the black brush bristles reach the height of the yellow indicator bristles replace the brush.



09) **Clean and rinse the brushes and brush housing.**



10) **Store brushes bearing-cap side up to allow them to dry.**



11) **Remove and clean the flood bar.**



12) **Take a clean rag and wipe down the exterior of the machine.**



13) **Plug the batteries back into the charger and maintain if necessary.**




14) **Vent recovery dome for storage.**

WINDSOR CHARIOT 3 | EXTRACT 26 DUO



OPERATION

86376040



01) Unplug the batteries from the charger and plug the batteries into the machine.



02) Reinstall the brushes into the brush housing.



03) Fill the solution tank with water and measured chemicals.



04) Put the key into the ignition and turn the machine on.



05) Step onto the grey platform.



06) Select the forward or reverse direction.



07) Select speed or mode of operation.

WINDSOR CHARIOT 3 iEXTRACT 26 DUO



OPERATION

86376040



08) Press the green pedal to move.



09) **IN CASE OF EMERGENCY:** press the red button to stop the machine.



10) Overlap 2-3" on every pass.



11) Shut off the water in tight turns.



Bold Innovation. Expert Results.



Bold Innovation. Expert Results.



Bold Innovation. Expert Results.