

WINDSOR



MAINTENANCE

86374210

CHARIOT 3 iSCRUB 26 SP



01) Drain and rinse recovery and solution tanks. Vent the recovery lid for storage.



02) Clean and rinse recovery tank, and inspect the float shut-off and clean as needed



03) Clean squeegee assembly and inspect the blades. If the squeegee is damaged or worn, flip the blade or replace



04) Remove and inspect brushes to clean and replace as necessary.



05) Clean and rinse sweep tray after every use



06) Take a clean rag and wipe down the exterior of the machine and vent tank lid for storage.



07) Plug the batteries back into the charger and maintain if necessary.

WINDSOR



OPERATION

86374210

CHARIOT 3 iSCRUB 26 SP




01) Unplug the batteries from the charger and plug the batteries into the machine.



02) Fill solution tank with water and measured chemicals. If equipped with chemical metering fill it with desired chemical. Make sure brushes and or pads are installed.



03) Make sure that the solution tank cap and recovery lid are closed properly and make sure latch is secured.



04) Put the key into the ignition and turn the machine on.



05) Choose operation mode. Clockwise starting at 1 o'clock: Eco-2, Normal, Heavy, Vacuum only, Water & Agitation only, Transport-1, Transport-2, Eco-1



06) Select direction (forward or reverse).



07) Step onto platform and press green pedal to move.

WINDSOR

CHARIOT 3 iSCRUB 26 SP



OPERATION

86374210



08) Overlap 2-3" on every pass.



09) IN CASE OF EMERGENCY:
press the red button to stop
the machine.



Bold Innovation. Expert Results.



Bold Innovation. Expert Results.



Bold Innovation. Expert Results.



Bold Innovation. Expert Results.



Bold Innovation. Expert Results.