WINDSOR

Voyager DUO and Commodore DUO



MAINTENANCE



01) Drain and rinse recovery

tank.



02) Clean float shut off.



03) Remove squeegee and inspect blades. If the squeegee is damaged, flip the blade or replace.



04) Clean squeegee.



05) Clean brushes.



06) INSPECT BRUSHES: When the height of the yellow indicator bristles replace the brush.



07) Remove jets and soak in a solution of hot water and vinegar overnight.

WINDSOR

VOYAGER DUO AND COMMODORE DUO



OPERATION 86372350



01) Unplug the batteries from the charger and plug the batteries into the machine.



02) Fill solution tank with extraction rinse or fresh water.



03) Inspect wheel for wear, brush for wear, and spray nozzles before operating.



04) Turn on the machine.



05) Choose mode of operation. From left to right: encapsulation, deep extraction and rinsing, and

accessory.



06) Press the blue button to turn
on the solution. When the
solution is on, the green button will illuminate.



07) Adjust speed to desired pace and set within the A range for encapsulation or B range for deep extraction and rinsing.

WINDSOR

VOYAGER DUO AND COMMODORE DUO



08) Press the green paddles to move the machine.



reverse the machine.





11) Plug the batteries back into the charger.





WINDSOR