

The FV Floor Maintainer

Rugged planetary drive system

Helical-cut gears for ultra smooth power transmission

Optional 4 gallon solution tank

- 1 Ergonomic, dihedral handle for operator comfort.
- 2 Dual, independent micro switches reduce down time.
- 3 Handle locking device insures safe operation.
- 4 1 hp motor with 1.25 service factor for extra power.
- 5 Die cast aluminum housing is five times stronger than sand castings.
- 6 360 degree non-marking, vinyl bumper protects walls and furniture.
- Machined steel, helical-cut planetary gears provide smooth transmission of power to the floor. Oversized bearings and seals give the gear unit decades of trouble-free performance.
- 8 Large, non-marking wheels.
- 9 Hospital grade plugs with soldered wires and hardened ground plug reduces cost and increases safety.
- Ohrome handle tube resists rust.
- Brass and steel strain relief protects the power cable.



RECOMMENDED PRODUCTS



Designed with the latest polymer and floor finish technology, OmniGuard™ produces a spectacular off-themop shine.



An economical neutral formula cleaner for all washable surfaces.
Cleans and deodorizes in a single step. Leaves a fresh lavender fragrance behind.

TECHNICAL DATA

Power Cable 50 ft

Operating FM17: 17" (43 cm) Width FM20: 20" (51 cm)

Pad Speed 175 rpm

Power Supply 115 V 1hp

Gear System Dual planetary

Weight FM17: 102 lb (47 kg) FM20: 107 lb (49 kg)

Engine: Parts & Labor - 2 yrs*
Warranty Machine: Parts & Labor - 1 yr*

*Excludes wear and maintenance items



AVAILABLE MODELS

FM17: 17" 115V FM20: 20" 115V

