



Commercial Floor Care Equipment

3500/3520 Wet Dry Vacuum



Features		Specifications
Product Name Model Number	3500 607673	3520 607674
Chassis/Body Construction Caster Diameter Wheel Diameter	Rotationally-molded polyethylene 4 in/ 10 cm 10 in/ 25 cm	Rotationally-molded polyethylene 4 in/ 10 cm 10 in/ 25 cm
Vacuum Recovery System Airflow at Orifice Water lift at Sealed Orifice: Vacuum Motor Horsepower: Vacuum Motor Amps: Vacuum Motor Diameter: Vacuum Motor Stages: Vacuum Motor Voltage: Vacuum Motor Watts: Recovery Tank Capacity: Vacuum Bag Capacity:	103 cfm/ 2.9 m ³ /hr 92 in/ 233 cm 1.3 hp 8.5 A 5.7 in/ 14 cm 2 Stage 120 V 980 Watts 15 gal/ 56 L 1/3 bushel/ L	100 cfm/ 2.9 m ³ /hr 120 in/ 233 cm 1.6 hp 10.7 A 5.7 in/ 14 cm 3 Stage 120 V 1242 Watts 15 gal/ 56 L 1/3 bushel/ 10 L
Dimensions Product Height: Product Length: Product Width: Product Weight:	37.5 in/ 95 cm 29 in/ 73 cm 15.5 in/ 39 cm 44 lb/ 20 kg	37.5 in/ 95 cm 29 in/ 73 cm 15.5 in/ 39 cm 44 lb/ 20 kg
Power Cord Power Cord Length	50 ft/ 15 m	50 ft/ 15 m
Accessories/Tools Standard	10 ft x 1.5 in/ 2 cm x 3 cm vacuum hose, standard drain hose. One cloth and one paper filter bag. Contractor tool kit: Dual bend aluminum wand.	
Optional Accessories	The 26 in/ 66 cm, 33 in/ 83 cm, or 39 in/ 99 cm Squeegee Attachment Kit.	



Warranty	Tennant warrants the rotationally-molded polyethylene housings and parts on all of its machines to be free from defects in materials and workmanship, under normal use and service for ten (10) years to the original end user. Under this warranty, we guarantee the performance of non-polyethylene parts and components to be free from defects for up to three (3) years or 2,500 hours of operation, whichever comes first, to the original end user. Parts replaced or repaired under this warranty are guaranteed for the remainder of the original warranty period. Labor charges are covered for three (3) full years form the date of purchase for Tennant models, provided an authorized Tennant service provider is used for repair.
-----------------	---

