



Model 750 Specifications

ALL SURFACE CLEANER

| Feature | | English / Metric |
|--------------------------------|--|------------------|
| Body Construction | | |
| Housing | Polyethylene | |
| Casters | 4-inch/ 100 mm | |
| Wheel type | 12-inch/ 305 mm | |
| Tank Capacity | | |
| Recovery tank capacity | 19 gallon/ 72 liter | |
| Solution tank capacity | 15 gallon/ 57 liter | |
| Solution Pump | | |
| Pressure | 500 psi/ 34 bar | |
| Voltage | 120 V | |
| Amps | 4.5 A | |
| High pressure setting | 1 gpm/ 300 psi / 4 lpm/21 bar | |
| Low pressure setting | 1.5 gpm/45 psi / 6 lpm/3 bar | |
| Machine Dimensions | | |
| Height | 37.5-inch/ 950 mm | |
| Length | 36.5-inch/ 925 mm | |
| Width | 18.5-inch/ 470 mm | |
| Weight | 126 lb/ 57 kg | |
| Recovery System | | |
| Motors (2) | 1 vacuum, 1 blower | |
| Vacuum water lift (vac/blower) | 117/91-inch/ 2972/2311 mm | |
| Airflow (vac/blower) | 99/104 cfm/ 168 m ³ /176 m ³ hour | |
| Vacuum motor type | Single speed, UL/CSA | |
| Motor stage (vac/blower) | 3-stage (vac), 2-stage (blower) | |
| 3-stage vacuum motor amps | 10 A | |
| Vac/blower motor voltage | 120 V | |
| Vac/blower motor watts | 1200/1000 W | |
| Power Cord | | |
| Description | Yellow, GFCI (120 V, 15 A) | |
| Total power consumption | 14.25 A | |
| Length | 25 ft/ 7.6 m | |
| Warranty | 3 YEARS/2500 HOURS PARTS AND LABOR. NO TRAVEL. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. PLEASE CALL FOR MORE WARRANTY INFORMATION | |