

# ORBITAL SCRUBBING

### Speed Scrub® Orbital Scrubber and Speed-SQ 14 Orbital Floor Machine

6

- Speed Scrub Orbital scrubs effectively with orbital motion and ec-H2O<sup>™</sup> technology
- Reach tight and confined areas easily with compact designs
- User-friendly designs for improved operator experience

Built to be **tough**. Made to be **easy**.



## **Chemical-Free Floor Finish Removal**



#### **Orbital Scrubbing**

- Rectangular scrub head reaches into corners and hard-to-reach areas easily for even floor finish removal across the entire cleaning path.
- Chemical-free floor finish removal alternative for VCT floors with the quality and reliability you expect from Nobles.

#### Speed Scrub® Orbital Scrubber

- With more down pressure, removes acrylic floor finish better than the leading competitor.
- Power and performance without the risks of chemicals.

#### Speed-SQ 14 Orbital Floor Machine

- Great for compact spaces.
- Two standard weight sets included at 48 lbs / 22 kg. Optional set available, adding an additional 24 lbs / 11 kg.
- Isolators reduce vibrations to the operator's hands, making operator comfort a priority.



Tennant Company Orbital Scrubbing is the smart, reliable choice for your no-nonsense cleaning needs.

#### Nobles

701 North Lilac Drive Minneapolis, MN 55422

USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050

www.nobles.com nobles@tennantco.com

1.608.001.am.en Orbital Scrubbing sell sheet 5/13 ©2013 The Tennant Company logo and other trademarks designated with the symbol "©" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors.

Orbital Scrubbing	Speed Scrub	Speed-SQ 14
Cleaning path	20 in (14 in x 20 in pad) / 51 cm (356 mm x 510 mm pad)	
Scrub motor	.60 HP / .45 kW	1.5 HP / 1.12 kW
Orbital Head Speed	2,200 rpm	1,740 rpm
Down pressure	63, 98 lbs / 27, 45 kg	n/a
Battery amp hour rating Wet (standard) AGM (optional)	(2) 12V, 155 AH (2) 12 V, 140 AH	n/a n/a
Power cord	n/a	50 ft / 15 m
Sound level (operator ear)	<70 dBA	
UL approval	n/a	yes

Specifications subject to change without notice