# Granterra™

Rider Sweeper



# Smart cleaning.



**A Nilfisk-Advance Brand** 

Technical Specifications	
Model	Granterra™
Sweep Path	66 in (167.6 cm) with single side brush or 78 in (198 cm) with dual side brushes
Power Source – LPG	74 hp GM 3.0 L
Power Source – Diesel	Mitsubishi 47.3 hp
Main Broom Length	50 in (127 cm)
Side Broom Length	24 in (61 cm)
Turning Radius Left	68 in (170 cm)
Turning Radius, Right	91 in (241 cm)
Hopper Capacity	27 ft <sup>3</sup> (0.76 m <sup>3</sup> ) 1,800 lb (816.4 kg)
Hopper Dump	Up to 63 in (152 cm)
Maximum Ramp Climb	12°
Size (L x W x H)	97 x 70.5 x 59.5 in (246.3 x 179 x 151 cm)
Weight	4,100 lb (1,860 kg)

• Tools-free dust filter changes

Two dust filters with total of

• Equipped with key switch

Hand operated parking brake

Simple to operate and easy

of filtering area

to maintain

fuel gauge

172 square feet (16 square meters)

Complete instrumentation features

hour and voltmeter, oil pressure,

water temperature and electric

Specifications are subject to change without notice.

## FEATURES AND BENEFITS

Design – Simplest, most comfortable sweeper to operate.

**Durability** – Reliable performance with proven technology and a long service life. Rugged construction with improved dust control system.

Productivity – Up to 78 in (198 cm) sweep path with a large capacity, high dump hopper.

### Standard features:

- Direct throw sweeping
- Hydraulic pump with cast iron housing
- Heavy gauge all steel construction
- Super duty, 21 in (53.3 cm) OD industrial tires
- Adjustable suspension seat with lower back support
- Full time power steering
- Single foot pedal controls forward and reverse direction
- Maneuvers in tight, congested areas

### Accessories and options:

- Overhead guard
- Preferred option package
- Safety lights
- Dual side brooms

Ask about our leasing options. ©2013 Nilfisk-Advance, Inc. Form L3054A 3-21-13

- SE air cleaner
- All weather cab available with air conditioning
- Heater, defroster
- Fire extinguisher and back up alarm system
- Various types of brooms

exposure to moving and high temperature componentsDebris transporter allows operator to move the move for any temperature temperature.

• Fully enclosed design minimizes

 Debris transporter allows operator to roll hopper forward to move debris forward, which maximizes the use of available hopper

> 14600 21st Avenue North Plymouth, MN 55447-3408 www.advance-us.com Phone 800-214-7700 Fax 800-989-6566

240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.ca Phone 800-668-8400 Fax 800-263-5111





A Nilfisk-Advance Brand